



Calle Melilla 1 Pol. Ind. Colomer APD 194
 12200 Onda (Castellón) Spain
 C.I.F. B12915211

BASIC CHARACTERISTICS:

Pieces name:	SAN CARLO GOLD SATIN XS (PRC)60X120
Size(cm):	60X120
Colour:	SATIN
Series name:	SAN CARLO
Family:	GLAZED PORCELAIN

TECHNICAL CHARACTERISTICS:

Fabrication process:	Dry pressed ceramic tile	
Absorption group (ISO 13006):	Bla	
Finish:	GL	
Rectified:	Yes	
Surface Finish:	Matt	
Pasta type:	Standard body	
Work size (mm):	600X1200X9	
Number of different designs:	4	
Aesthetic classification and shade variations:	V.2	
Facial dimension range and surface quality:	meets the standard	UNE EN ISO 10545-2

PHYSICAL CHARACTERISTICS:

Water absorption:	E = 0.5	UNE EN ISO 10545-3
Braking strenght (S):	> 1300N	UNE EN ISO 10545-4
Flexural tensile strenght (N/mm2):	=35 N/mm2	
Resistance to surface abrasion: (PEI)	4	UNE EN ISO 10545-7
Lineal thermal expansion between 20° to 100°C:	meets the standard	UNE EN ISO 10545-8
Thermic shock resistance:	meets the standard	UNE EN ISO 10545-9
Crazing resistance:	meets the standard	UNE EN ISO 10545-11
Durability; Freeze - thaw cycle:	meets the standard	UNE EN ISO 10545-12
Scratch hardness according to MOHS:	6	UNE EN ISO 67-101-92
Slipperness:	Anti-slip class 1	UNE ENV 41901
		DIN 51130

CHEMICAL PROPERTIES:

Resistance to chemicals and pool treatment products:	meets the standard	UNE EN ISO 10545-13
Resistance to high concentration acids and bases:	HB	
Resistance to low concentration acids and bases:	LB	
Resistance to staining:	meets the standard	UNE EN ISO 10545-14

CE MARKING:

IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed.

Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process.

Document with commercial information and cannot be used either judicially or administratively without the express premission of Mykonos Mosaic S.L. The color of the tile of this technical data is for guidance only and may differ from the actual tile color.

09/12/2022

31/10/2022

JEFE DE PRODUCTO
 JEFE DE PRODUCTO



Calle Melilla 1 Pol. Ind. Colomer APD 194
12200 Onda (Castellón) Spain
C.I.F. B12915211



BASIC CHARACTERISTICS:

Pieces name:	SAN CARLO GOLD SATIN XS (PRC)60X120
Size(cm):	60X120
Colour:	SATIN
Series name:	SAN CARLO
Family:	GLAZED PORCELAIN

TECHNICAL CHARACTERISTICS:

Fabrication process:	Dry pressed ceramic tile	
Absorption group (ISO 13006):	Bla	
Finish:	GL	
Rectified:	Yes	
Surface Finish:	Matt	
Pasta type:	Standard body	
Work size (mm):	600X1200X9	
Number of different designs:	4	
Aesthetic classification and shade variations:	V.2	
Facial dimension range and surface quality:	meets the standard	UNE EN ISO 10545-2

PHYSICAL CHARACTERISTICS:

Water absorption:	E = 0.5	UNE EN ISO 10545-3
Braking strenght (S):	> 1300N	UNE EN ISO 10545-4
Flexural tensile strenght (N/mm2):	=35 N/mm2	
Resistance to surface abrasion: (PEI)	4	UNE EN ISO 10545-7
Lineal thermal expansion between 20º to 100ºC:	meets the standard	UNE EN ISO 10545-8
Thermic shock resistance:	meets the standard	UNE EN ISO 10545-9
Crazing resistance:	meets the standard	UNE EN ISO 10545-11
Durability; Freeze - thaw cycle:	meets the standard	UNE EN ISO 10545-12
Scratch hardness according to MOHS:	6	UNE EN ISO 67-101-92
Slipperness:	Anti-slip class 1	UNE ENV 41901
		DIN 51130

CHEMICAL PROPERTIES:

Resistance to chemicals and pool treatment products:	meets the standard	UNE EN ISO 10545-13
Resistance to high concentration acids and bases:	HB	
Resistance to low concentration acids and bases:	LB	
Resistance to staining:	meets the standard	UNE EN ISO 10545-14

CE MARKING:



IMPORTANT NOTES:

Before fixing tiles, please check the shade, calibre and choice. Claims regarding these items cannot be accepted once the materials has been fixed.

Protecting the product during placement and appropriate cleaning after grouting and other work are part of a correct fitting process.

Document with commercial information and cannot be used either judicially or administratively without the express premission of Mykonos Mosaic S.L. The color of the tile of this technical data is for guidance only and may differ from the actual tile color.

09/12/2022